

MATERIAL SAFETY DATA SHEET

P.O. BOX 1603 EUNICE, LA 70535 866-457-0064 or 337-457-0064

CALCIUM CARBONATE FINE

SECTION I - IDENTIFICATION

Manufacturer's Name: Delta Drilling Products & Services, LLC

Physical Address: 154 Eastpark Drive

Eunice, LA 70535

Emergency Number: 866-457-0064 or 337-457-0064
Product Name(s): Lime (Calcium Hydroxide)
Chemical Family: Calcium Hydroxide
Trade Name: Calcium Carbonate, CaCo₂

SECTION II – INGREDIENTS

Principal Hazardous Ingredients: None (Observe nuisance dust precautions).

SECTION III – PHYSICAL DATA

Boiling Point: Not Available

Specific Gravity: 2.3-2.4

Vapor Pressure: Not Available pH: 11.0-12.0

Vapor Density: Not Available Evaporation Rate: Not Available Solubility in Water: Appreciable

Appearance: White Powder/Crystals. Mild odor.

SECTION IV - FIRE & EXPLOSION HAZARD DATA

Flash Point: Not Available

Extinguishing Media: Foam, CO₂, dry chemical

Unusual Fire & Explosion Hazards: None known Special Fire Fighting Procedures: None known

SECTION V - HEALTH HAZARD DATA

Routes of Entry: Entry into body is not expected when observing industrial hygiene procedures.

Carcinogenicity: Not listed as a carcinogen by NTP, OSHA or IARC.

TLV: Not Available

Emergency First Aid Procedures: In case of contact with eyes, flush with plenty of fresh water.

Effects of Overexposure: Not Available

SECTION VI - REACTIVITY DATA

Stability: Stable

Conditions to Avoid:
Incompatibility (Materials to Avoid):
Hazardous Decomposition Products:
Hazardous Polymerization:

Sources of high heat
Strong oxidizers
Not Available
Will not occur

SECTION VII - SPILL OR LEAK PROCEDURES

Steps In Case of Spilled or Released Material: Sweep up into container. Recycle, if possible.

Waste Disposal Method: Disposal in industrial landfill, according to applicable laws.

SECTION VIII - SPECIAL PROTECTION INFORMATION

Appropriate Hygienic Practices: Avoid direct contact with eyes, skin and mouth.

Personal Protection Equipment: Chemical safety glasses, OSHA approved respirator and chemical rubber

gloves. Face

shield may be needed.

Ventilation: Local or mechanical exhaust.

Other Protective Measures: Avoid spillage as floors may become slippery. Store in sealed container.

SECTION IX - ADDITIONAL INFORMATION

NFPA Hazard Rating: Fire -0

Reactivity -1Toxicity -1Other -0

0 = Minimal 1 = Slight 2 = Moderate 3 = Severe 4 = Extreme

The information herein is furnished without warranty of any kind. Employers should use this information only as supplemental to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. DELTA DRILLING PRODUCTS & SERVICES, LLC assumes no responsibility and denies all liability for any loss, damage or expense connected with the customers methods of handling, storage, use and disposal of this product.

